



BL 4800
BL 6800



BL 8800



- Robust and durable construction
- Easy to use and transport
- High air flow
- Possibility to connect flexible ducts
- Rotomoulded casing

Optional accessories



PVC flex tubes 7.6m
BL 4800 - Ø210mm -
4160.251
BL 6800 - Ø305mm -
4031.406
BL 8800 - Ø407mm -
4031.402



Dust bag -
3m length
BL 4800 - **4515.540**
BL 6800 - **4515.541**
BL 8800 - **4515.542**
Dust bag filtration
level - EPA 10

Specifications	Units	BL 4800	BL 6800	BL 8800
Air flow	m ³ /h	750	3,900	7,800
Max. air pressure	Pa	245	388	496
Fan	type	Axial	Axial	Axial
Fan speed		1	1	1
Power consumption	W	250	750	750
Power supply	V/Hz	220-240/1ph/50	220-240/1ph/50	220-240/1ph/50
Outlet diameter	Ømm	200	300	400
Air current		Blow out/suction	Blow out/suction	Blow out/suction
Protection		IP44	IP44	IP44
Product size (l x w x h)	mm	340 x 250 x 370	470 x 370 x 520	510 x 530 x 580
Box size (l x w x h)	mm	370 x 270 x 390	510 x 400 x 525	560 x 550 x 600
Net/gross weight	kg	7.2/7.7	14.7/15.9	19/20
Pallet	pcs	40	16	6